







- Shielded
- Suited for both EMC and energy storage using (filters, SMPS, etc.)
- Tape & Reel packaging
- Others values on request



Code	Nominal Inductance <sup>1</sup>	Nominal Current <sup>2</sup>	Max DCR <sup>3</sup>
SLDS12051R3F	1.3 µH	8.00 A	12 mΩ
SLDS12052R1F	2.1 µH	7.00 A	14 mΩ
SLDS12053R1F	3.1 µH	6.00 A	17 mΩ
SLDS12054R4F	4.4 µH	5.00 A	20 mΩ
SLDS12055R8F	5.8 µH	4.40 A	21 mΩ
SLDS12057R5F	7.5 µH	4.20 A	24 mΩ
SLDS1205100F	10 µH	4.00 A	25 mΩ
SLDS1205120F	12 µH	3.50 A	27 mΩ
SLDS1205150F	15 µH	3.30 A	30 mΩ
SLDS1205180F	18 µH	3.00 A	34 mΩ
SLDS1205220F	22 µH	2.80 A	36 mΩ
SLDS1205270F	27 µH	2.30 A	51 mΩ
SLDS1205330F	33 µH	2.10 A	57 mΩ
SLDS1205390F	39 µH	2.00 A	68 mΩ
SLDS1205470F	47 µH	1.80 A	75 mΩ
SLDS1205560F	56 µH	1.70 A	110 mΩ
SLDS1205680F	68 µH	1.50 A	120 mΩ
SLDS1205820F	82 µH	1.40 A	140 mΩ
SLDS1205101F	100 µH	1.30 A	160 mΩ
SLDS1205121F	120 µH	1.10 A	170 mΩ
SLDS1205151F	150 µH	1.00 A	230 mΩ
SLDS1205181F	180 µH	0.90 A	290 mΩ
SLDS1205221F	220 µH	0.80 A	400 mΩ
SLDS1205271F	270 µH	0.75 A	460 mΩ
SLDS1205331F	330 µH	0.68 A	510 mΩ
SLDS1205391F	390 µH	0.65 A	690 mΩ
SLDS1205471F	470 µH	0.58 A	770 mΩ
SLDS1205561F	560 µH	0.54 A	860 mΩ
SLDS1205681F	680 µH	0.48 A	1.20 Ω
SLDS1205821F	820 µH	0.43 A	1.34 Ω
SLDS1205102F	1000 µH	0.40 A	1.53 Ω

Dimensions	mm	Drawing
a max	12.3	
b max	12.3	
h max	6.0	
c typ	11.8	
d typ	5.0	
e typ	7.6	

<sup>1</sup> Tolerances ±30% - Measured @100KHz-100mV up to 9.9µH | tolerances ±20% - Measured @1KHz-100mV 10µH or more

<sup>2</sup> Max continuous DC current for 40°C temperature rise and 25% max inductance drop

<sup>3</sup> Referred to 20°C.

## SLDS1207 series - 1.2µH...1.0mH 9.8A...550mA

- Shielded
- Suited for both EMC and energy storage using (filters, SMPS, etc.)
- Tape & Reel packaging
- Others values on request



Code	Nominal Inductance <sup>1</sup>	Nominal Current <sup>2</sup>	Max DCR <sup>3</sup>
SLDS12071R2F	1.2 µH	9.80 A	7 mΩ
SLDS12072R4F	2.4 µH	8.00 A	12 mΩ
SLDS12073R5F	3.5 µH	7.50 A	14 mΩ
SLDS12074R7F	4.7 µH	6.80 A	16 mΩ
SLDS12076R1F	6.1 µH	6.60 A	18 mΩ
SLDS12077R6F	7.6 µH	5.90 A	20 mΩ
SLDS1207100F	10 µH	5.40 A	22 mΩ
SLDS1207120F	12 µH	4.90 A	24 mΩ
SLDS1207150F	15 µH	4.50 A	30 mΩ
SLDS1207180F	18 µH	3.90 A	39 mΩ
SLDS1207220F	22 µH	3.60 A	43 mΩ
SLDS1207270F	27 µH	3.40 A	46 mΩ
SLDS1207330F	33 µH	3.00 A	65 mΩ
SLDS1207390F	39 µH	2.75 A	73 mΩ
SLDS1207470F	47 µH	2.50 A	100 mΩ
SLDS1207560F	56 µH	2.35 A	110 mΩ
SLDS1207680F	68 µH	2.10 A	140 mΩ
SLDS1207820F	82 µH	1.95 A	160 mΩ
SLDS1207101F	100 µH	1.70 A	220 mΩ
SLDS1207121F	120 µH	1.60 A	250 mΩ
SLDS1207151F	150 µH	1.42 A	280 mΩ
SLDS1207181F	180 µH	1.30 A	350 mΩ
SLDS1207221F	220 µH	1.16 A	390 mΩ
SLDS1207271F	270 µH	1.06 A	560 mΩ
SLDS1207331F	330 µH	0.95 A	640 mΩ
SLDS1207391F	390 µH	0.88 A	700 mΩ
SLDS1207471F	470 µH	0.79 A	980 mΩ
SLDS1207561F	560 µH	0.73 A	1.07 Ω
SLDS1207681F	680 µH	0.67 A	1.46 Ω
SLDS1207821F	820 µH	0.60 A	1.64 Ω
SLDS1207102F	1000 µH	0.55 A	1.82 Ω

Dimensions	mm	Drawing
a max	12.3	
b max	12.3	
h max	8.0	
c typ	12.0	
d typ	5.0	
e typ	7.6	

<sup>1</sup> Tolerances ±30% - Measured @100KHz-100mV up to 9.9µH | tolerances ±20% - Measured @1KHz-100mV 10µH or more

<sup>2</sup> Max continuous DC current for 40°C temperature rise and 25% max inductance drop

<sup>3</sup> Referred to 20°C.