

UI series U3921 - 30VA

- Safety transformers according to the European standard CEI EN 61558-1 and CEI EN 61558-2-6
- Primary and Secondary two chamber windings
- Encapsulation in epoxy resin
- Marking on primary side
- Tin-plated phosphor bronze pins
- Pins size: $\varnothing 0,9$ mm typ , length 4mm min
- Only electrically used pins are mounted
- 5000V dielectric strength between primary and secondary windings
- 100% tested
- Custom-made versions on request
- Fixing with 4 self-tapping screws 3x16mm



30 VA - t_a50/B



Code	Primary (50-60Hz)	Secondary ¹	Output fuses ²
U3921S06	2x115V	2x 6V - 2500 mA	2 fuses 2500 mA
U3921S09	2x115V	2x 9V - 1666 mA	2 fuses 2000 mA
U3921S12	2x115V	2x 12V - 1250 mA	2 fuses 1250 mA
U3921S15	2x115V	2x 15V - 1000 mA	2 fuses 1000 mA
U3921S18	2x115V	2x 18V - 883 mA	2 fuses 1000 mA

Dimensions	mm	Layout (bottom view)	Drawing
a max	68,6		
b max	57,7		
h max	35,8		
x typ	5,0		
x1 typ	6,0		
y typ	45,0		
c typ	62,6		
d typ	50,2		

230V / 2xVsec	230V / 2xIsec	115V / 2xVsec	115V / 2xIsec
Primary double voltage Secondary double voltage	Primary double voltage Secondary double current	Primary double current Secondary double voltage	Primary double current Secondary double current

¹ Rated voltage (No load voltage x 1,19).

² See the output fuses notes on back cover. Different overload protection are possible if the user performs proper tests to assure the relevant standard compliance.